



- ◆ H.264 Compression Technology,
- ◆ Real Time Recording
- ◆ HDMI and VGA output at up to 1920 × 1080 resolution
- ◆ User Friendly True Color GUI
- ◆ 4CH/8CH synchronous playback
- ◆ Supports 2 SATA Devices

SPECIFICATION

Model		LDVR-SDI04A	LDVR-SDI08A
Video/Audio input	Video compression	H.264	
	HD-SDI video input	4-ch	8-ch
		HD-SDI interface	
	Audio compression	G.711u	
	Audio input	4-ch	8-ch
RCA (2.0 Vp-p, 1 KΩ)			
Two-way audio in	1-ch, RCA (2.0 Vp-p, 1 KΩ), (using the 1 st channel of audio input)		
Video/Audio output	HDMI / VGA output	1920 × 1080 / 60 Hz (1080P), 1280 × 1024 / 60 Hz, 1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz	
	Encoding resolution	Main stream: 1920 × 1080 (1080P) / 1280 × 720 / VGA / 4CIF / CIF	
		Sub-stream: 4CIF(non-real-time) / CIF / QCIF / QVGA	
	Frame rate	Main stream: 1/16 fps ~ Real time frame rate	
		Sub-stream: 1/16 fps ~ Real time frame rate	
	Video bitrate	32 Kbps-16 Mbps	
	Audio output	1-ch, RCA (Linear, 1KΩ)	
	Audio bitrate	64 Kbps	
	Dual-stream	Support	
	Stream type	Video, Video & Audio	
Synchronous playback	2-ch, 1080P / 4-ch, 4CIF	2-ch, 1080P / 8-ch, 4CIF	
Playback resolution	1920 × 1080 (1080P) / 1280 × 720 / VGA / 4CIF / CIF		

SPECIFICATION

Model		LDVR-SDI04A	LDVR-SDI08A
Remote access	Output bandwidth	128Mbps	256Mbps
	Remote connections	128	
Network management	Network protocols	TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™	
Hard disk	SATA	2 SATA interfaces	
	Capacity	Up to 4 TB capacity for each disk	
External interface	Network interface	1; 10M / 100M / 1000M self-adaptive Ethernet interface	
	Serial interface	1; standard RS-485 serial interface, half-duplex	
	USB port	2 x USB2.0	
	Alarm in / out	4 / 1 (optional)	
General	Power supply	12V DC	
	Consumption (without hard disks)	Max. 15 W	Max. 20 W
	Working temperature	-10 °C ~+55 °C (14 °F ~ 131 °F)	
	Working humidity	10% ~ 90%	
	Chassis	19-inch rack-mounted 1U chassis	
	Dimensions (W x D x H)	445 x 290 x 45 mm (17.5 x 11.4 x 1.8 inch)	
	Weight	4 kg / 8.8lb (without hard disk)	