

## LHD-22P5

## HD-SDI Vari-Focal DOME CAMERA

### Product Feature

- Panasonic 2.1 Mega Pixel CMOS sensor
- Full HD resolution up to 1920 x 1080
- 2.8 - 12mm Adjustable Angle Lens
- OSD menu with 3DNR, White Balance, Image & various adjustment
- Accurate color performance
- True Day & Night function with ICR module
- Support dual video format: PAL / NTSC



|   |  |
|---|--|
| <b>Model</b>                              | LHD-22P5                                   |
| <b>Image Sensor</b>                       | Panasonic 1/3" 2.1 Megapixel CMOS Sensor   |
| <b>Scanning System</b>                    | Progressive Scan                           |
| <b>Resolution</b>                         | 1080p, 1920 x 1080 (30FPS)                 |
| <b>Sensitivity (F1.2)</b>                 | 1.0 Lux                                    |
| <b>Lens</b>                               | 2.8-12mm, 3 Megapixel                      |
| <b>Effective Pixels (H x V)</b>           | 1944(H) x 1092(V)                          |
| <b>S/N Ratio</b>                          | >50dB                                      |
| <b>Video Output (BNC Type)</b>            | HD-SDI: 1.485G/s (SMPTE292M), 1.0Vp-p~75Ω  |
| <b>Day / Night</b>                        | AUTO(ICR) / COLOUR / B&W / EXT             |
| <b>3D Noise Reduction</b>                 | ON / OFF                                   |
| <b>O.S.D.</b>                             | YES, Built-in                              |
| <b>Gain Control</b>                       | OFF / LOW / MID / HIGH                     |
| <b>White Balance</b>                      | ATW / AWCàSET / INDOOR / OUTDOOR / MANUAL  |
| <b>Back Light Compensation</b>            | OFF / BLC / HSBLC                          |
| <b>Shutter</b>                            | 1/30 / 1/60(1/50) / FLK / 1/250....1/50000 |
| <b>IR LED &amp; Illumination Distance</b> | N.A.                                       |
| <b>Operating Conditions</b>               | Temp: -10°C ~ +45°C, Humidity: 95% RH      |
| <b>Power Supply</b>                       | DC 12V ±10%                                |
| <b>Power Consumption</b>                  | IR OFF 300mA (Max)                         |
| <b>Dimensions</b>                         | Ø105mm x 90mm                              |
| <b>Weight</b>                             | 300g                                       |